



**NOW FEATURING**

**Our Patented Galvanized Cable.  
*An industry first!***

## Trackman® for John Deere®

Rubber Track

We are covering new ground with our expanded lineup for the John Deere® 8RT and 9RT models

### Standard agricultural track and ultra aggressive agricultural track enhancements

- › Ten percent more cable makes a more durable track with a stronger carcass. With 5.3mm cables, our longer life tracks lead the marketplace.
- › Patented galvanized corrosion-resistant cable also increases the life of the carcass.
- › The stronger carcass foundation reduces internal track temperatures, improves tread lug performance and tread wear life.
- › By doubling the wire, tread wear and track performance improve dramatically.

### Additional design features on our ultra aggressive agricultural track

- › Increased tread height and width puts more tread on the ground for longer tread wear life.
- › Tread design promotes lug strength and enables better clean out.
- › Thicker carcass provides a stronger foundation and optimizes the benefits of the new tread design.

### Our warranty is on track with your needs

In accordance with the Continental ContiTech Trackman® Rubber Track warranty, the track is covered against material and/or workmanship defects. For complete warranty information, contact your Rubber Track dealer or visit our website at [www.contitech.us/rubbertrack](http://www.contitech.us/rubbertrack).

Trackman®

**ContiTech**

## Rubber Track

**Trackman**® Rubber Track Specifications for John Deere® Tractors

Product Code	Vehicle	Description	Width (in.)	Length (in.)	# of Tread Lugs	Tread Pitch (in.)	Tread Lug Height (in.)	# of Guide Lugs	# of Wire Plies	Carcass Thickness (in.)	Ship Weight (lb.)
<b>John Deere® 8000T</b>											
703527850	JOHN DEERE® 8000T	Standard Ag.	16	324	108	6.0	2.0	54	3	1.25	873
703528240	JOHN DEERE® 8000T	Standard Ag.	18	324	108	6.0	2.0	54	3	1.25	943
703613530	JOHN DEERE® 8000T	Ultra Ag.	16	325	84	7.7	2.75	42	4	1.50	969
703613540	JOHN DEERE® 8000T	Ultra Ag.	18	325	84	7.7	2.75	42	4	1.50	1068
703527860	JOHN DEERE® 8000T	Standard Ag.	24	324	108	6.0	2.0	54	3	1.25	1147
703527870	JOHN DEERE® 8000T	Standard Ag.	30	324	108	6.0	2.0	54	3	1.25	1356
703612830	JOHN DEERE® 8000T	Ultra Ag.	24	324	72	9.0	2.75	54	4	1.50	1360
703612760	JOHN DEERE® 8000T	Ultra Ag.	30	324	72	9.0	2.75	54	4	1.50	1636
<b>John Deere® 9000T</b>											
703612770	JOHN DEERE® 9000T	Ultra Ag.	30	378	84	9.0	2.75	84	3	1.50	1952
703612780	JOHN DEERE® 9000T	Ultra Ag.	36	378	84	9.0	2.75	84	3	1.50	2198
<b>John Deere® 8RT</b>											
703612140	JD 8295RT/8320RT/8345RT	Standard Ag.	16	354	118	6.0	2.0	59	4	1.25	868
703612150	JD 8295RT/8320RT/8345RT	Standard Ag.	18	354	118	6.0	2.0	59	4	1.25	949
703613510	JD 8295RT/8320RT/8345RT	Ultra Ag.	16	357	92	7.7	2.75	46	4	1.50	985
703613520	JD 8295RT/8320RT/8345RT	Ultra Ag.	18	357	92	7.7	2.75	46	4	1.50	1094
703613920	JD 8295RT/8320RT/8345RT	Ultra Ag.	24	357	78	9.0	2.75	78	4	1.50	1490
703613930	JD 8295RT/8320RT/8345RT	Ultra Ag.	30	357	78	9.0	2.75	78	4	1.50	1776
<b>John Deere® 9030T/9RT</b>											
703612230	JD 9430T/9530T/9630T	Ultra Ag.	30	387	86	9.0	2.75	86	4	1.50	1952
703612240	JD 9430T/9530T/9630T	Ultra Ag.	36	387	86	9.0	2.75	86	4	1.50	2198

Trackman is a registered trademark of Continental ContiTech. John Deere® is a registered trademark of Deere and Company. Continental ContiTech is manufactured and sourced exclusively by Continental ContiTech or its affiliates. Copyright © 2014 ContiTech AG. All rights reserved. For complete information go to: [www.contitech.de/disc/en](http://www.contitech.de/disc/en)

20793487



### ContiTech

NAFTA Headquarters  
1-877-394-0482  
[www.contitech.us](http://www.contitech.us)  
[trackingquires@contitech.us](mailto:trackingquires@contitech.us)

ContiTech